

CHEMICAL & PETROCHEMICAL PACKAGING

High stability & protection for your polymers, granules, grouts, flakes, powders & other materials



PE Form-Fill-Seal (FFS)

- Mono or co-extruded PE films for packing building materials, compounds, fertilizers, flakes, granules, polymers, powders & salt
- Thickness: 40 - 300 microns
- Length: Customized
- Width: 40 - 100 cm
- Core inner diameter: 76 - 152 mm
- Printing up to 8 colors
- Perforation & embossing available
- Material blend specifically tailored to suit your packaging needs



PE Valve Bags

- One or two-ply PE valve bags for packing chemicals & masterbatches
- Thickness: 130 - 300 microns
- Bag length: 49 - 130 cm
- Unwinder width: 38 - 70 cm
- Bottom width: 9.5 - 18 cm
- Tube length: 59 - 151 cm
- Printing: Up to 8 colors & two sides
- Protection against sun radiation with UV treatment
- Perforated or embossed



PE Shrink Hood Films

- Plain or printed plastic shrink hood film in rolls & bags to ensure pallet stabilization & unitization
- Product protection against shock & sun radiation with UV stabilization
- Resistance to high heat & punctures
- Length: 20 - 225 cm
- Width: 15 - 140 cm
- Thickness: 45 - 150 microns

PE Stretch Hood Films

- Co-extruded plastic film for high-speed automatic machines
- Plain PE stretch hood film in rolls for cost-effective wrapping with outstanding quality
- High stretching ratios without mechanical failure
- High holding forces for pallet stability with protection

CHEMICAL & PETROCHEMICAL PACKAGING

High stability & protection for your polymers, granules, grouts, flakes, powders & other materials



Multi-Wall Paper Sacks

- Paper valve bags, PE coated paper sacks or paper sacks with PE liner for packing cement, gypsum, other building materials, petrochemicals & chemicals
- Length: 32 - 85 cm
- Width: 24 - 60 cm
- Bottom & valve: 7 - 22 cm
- Plies: 2 - 4
- Open top, pinched bottom, protruding valve, ultrasonic valve, reinforced valve, tubular valve, 5 kg handle bags or 10 kg multiwall sacks



Bitumen Membranes

- HDPE film in rolls & liners or packing hot asphalt, coal tar & high temperature products
- Thickness: 7 - 30 microns
- Length: 10,000 - 20,000 m
- Width: 102 - 106 cm
- Excellent chemical & electrical insulation resistance
- Very low water absorption
- Minimum shrinking during coupling process
- Resistance to high & low temperatures

Polyamide or Bitumen Bags

- Tubular polyamide bags enduring high bitumen temperatures up to 200°C
- Thickness: 60 microns
- Length: 90 cm
- Width: 40 cm
- Very low water absorption during the cooling process
- Customized printing for branding product positioning



Octabin Liners (Polyamide) for Packaging PVC Powder

- Length (range): 60 - 350 cm
- Width (range): 100 - 205 cm
- Thickness (range): 85 - 100 microns

CHEMICAL & PETROCHEMICAL PACKAGING



Indevco Paper Containers
A division of INDEVCO group

High stability & protection for your polymers, granules, grouts, flakes, powders & other materials



Heavy-Duty Corrugated Bulk Bins

- Sizes: 800 x 1200 mm or 1000 x 1200 mm footprint for optimized pallet handling
- Board basis weight: 450 - 2300 gsm
- Support up to 1500 kg
- Double or triple wall
- Weight advantages over wooden crates
- Suitable for solid or liquid materials
- Customized according to your requirements

